
Stainless Steel Drying Hoppers

Uniform drying coupled with easy accessibility for cleaning are key to proper hopper design

- Standard sizes range from 5 to 2000 lbs (2 to 907 kg); based on 35 lbs/ft^{3*}
- Dry less than half a hopper of material due to our unique diffuser basket design so there is no scrap
- Laser-cut access doors provide a smooth, tight fit and eliminates troublesome gaskets







, , , , , , , , , , , , , , , , , , , ,								
			DIMENSIO				N S	
Dri-Air Hopper	CAPACITY		A		В		C	
Model	lbs kg		in	cm	in	cm	in	cm
RH5	5 2		8	20	6	15	12	31
RH15	15 7		10	25	9	23	18	41
RH30	30 14		14	36	16	41	28	711
RH60	60 27		14	36	28	71	40	102
RH100	100 45		18	46	25	64	37	94
RH150	150 68		18	46	38	97	50	127
RH200	200 91		23	58	30	76	47	119
RH300	300 136		23	58	44	112	61	155
RH400	400 181		27	69	40	102	60	152
RH600	600 272		27	69	60	152	80	203
RH1000	1000 453		36	91	58.5	149	84.5	215
RH1500	1500 680		39	99	70.5	179	97	246
RH2000	2000 907		39	99	94.5	240	121	307

Note: RH5, RH15, and RH30 do not have access doors. *Larger hoppers available, consult factory.



Adjustable fill sensor option ties into hopper loader to accommodate varying process rates



RHfeatures

Exclusive basket design assures dried material down to the slide gate

- no slugs of undried material

No tools required for hopper cover

Internal ring on hopper cover prevents damage to hopper loaders

Easy-close slide gate on RH400

Insulated side walls eliminate heat

thru RH2000 hoppers

loss and conserve energy

www.dri-air.com